This listing of claims will replace all prior versions, and listing. Of claims in the present application:

## Listing of the claims:

1. (Withdrawn) A bone tap for introducing bone filler into a bone and for forming a threaded hole in the bone, comprising:

a body;

a passage through at least a portion of the body;

threading located near an end of the body; and

one or more openings through the threading in communication with the passage, the one or more openings configured to introduce bone filler into the bone.

- 2. (Withdrawn) The bone tap of claim 1, wherein the passage and at least one of the openings is configured to allow delivery of fluid to the bone during use.
- 3. (Withdrawn) The bone tap of claim 1, further comprising at least one flute formed in the threading adjacent to one of the openings.
- 4. (Withdrawn) The bone tap of claim 1, wherein the threading is configured to inhibit backflow of fluid along the body.
- 5. (Withdrawn) The bone tap of claim 1, further comprising a fluid port configured to form a seal with a fluid delivery system configured to introduce fluid into the passage.
- 6. (Withdrawn) The bone tap of claim 1, further comprising a tool portion configured to couple to a driver that facilitates insertion of the body into bone.

U.S. Patent Application No.: 10/717,379 Attorney Docket No.: 7177US01 Amendment Dated October 22, 2008 Page 3 of 16

- 7. (Withdrawn) The bone tap of claim 1, wherein the passage extends from a proximal end of the tap to a distal end of the tap.
- 8. (Withdrawn) The bone tap of claim 1, wherein the one or more openings comprises a plurality of fenestrations, wherein three or more fenestrations are spaced at substantially regular intervals along the threading.
  - 9. (Withdrawn) A surgical system for treating a bone, comprising: a tap comprising a passage and one or more openings; a driver configured to be coupled to the tap; at least one dilator configured to provide access to the bone; and a bone fastener,

wherein the passage and at least one of the openings are adapted to allow delivery of a fluid to the bone during use, and

wherein the bone fastener is configured to be inserted into a threaded opening created by the tap.

- 10. (Withdrawn) The system of claim 9, wherein the fluid comprises bone cement.
- 11. (Withdrawn) The system of claim 9, wherein the driver comprises a resilient member adapted to inhibit unintentional separation of the driver from the tap.
  - 12. (Withdrawn) The system of claim 11, wherein the resilient member is a spring tab.
- 13. (Withdrawn) The system of claim 9, wherein the tap further comprises a fluid port.
  - 14. (Withdrawn) The system of claim 9, further comprising a fluid delivery system.
  - 15.-20. (Cancelled).

U.S. Patent Application No.: 10/717,379
Attorney Docket No.: 7177US01
Amendment Dated October 22, 2008
Page 4 of 16

- 21. (Withdrawn) The bone tap of claim 1, wherein the bone filler is a bone adhesive.
- 22. (Withdrawn) The bone tap of claim 1, wherein the end of the body is blunt.
- 23. (Currently Amended) A method of introducing a fluid into a bone, comprising:

advancing preparing an opening in a bone using a bone tap into the bone, the bone tap comprising a body, a passage, one or more openings communicating with the passage, and threading located near an end of [[a]] the body of the bone tap;

introducing a fluid to the bone through at least one of the openings of the bone tap;

allowing the fluid to spread to a portion of the bone; and introducing a bone fastener into [[an]] the opening in the bone formed by the bone tap.

- 24. (Previously Presented) The method of claim 23 wherein the fluid comprises bone cement.
- 25. (Previously Presented) The method of claim 23, wherein the fluid comprises a bone filler and a medicament.
- 26. (Currently Amended) The method of claim 23, wherein advancing preparing the opening in the bone using the bone tap into the bone further comprises attaching a driver to the bone tap, placing the bone tap at an initial opening formed in the bone, and rotating the bone tap to thread the bone tap into the bone.
- 27. (Currently Amended) The method of claim 23, wherein introducing the fluid to the bone comprises coupling a fluid delivery system to the bone tap, and activating the fluid delivery system to move fluid through the bone tap and into the bone.
- 28. (Previously Presented) The method of claim 23, further comprising coupling a driver to the bone tap, and using the driver to remove the bone tap from the bone.

U.S. Patent Application No.: 10/717,379 Attorney Docket No.: 7177US01 Amendment Dated October 22, 2008 Page 5 of 16

- 29. (Cancelled).
- 30. (Withdrawn) The bone tap of claim 1, wherein the body comprises indicia for monitoring insertion depth of the bone tap into the bone.
- 31. (Currently Amended) The method of claim 23, wherein the step of introducing the fluid to the bone comprises the steps of: (1) introducing the fluid to a first location; (2) moving the bone tap; and (3) introducing the fluid to a second location.
- 32. (Previously Presented) The method of claim 31, wherein the step of moving the bone tap comprises partially withdrawing the bone tap.
  - 33. (Currently Amended) A method of introducing a fluid into a bone, comprising:

    advancing preparing an opening in a bone using a bone tap into the bone, the bone
    tap comprising a body, a passage, one or more openings communicating with the passage,
    and threading located near an end of [[a]] the body of the bone tap;

introducing a fluid to the bone through at least one of the openings of the bone tap;

allowing the fluid to spread to a portion of the bone; and coupling a removable driver to the bone tap, and using the driver to remove the bone tap from the bone.

- 34. (Previously Presented) The method of claim 33, wherein the fluid comprises bone cement.
- 35. (Previously Presented) The method of claim 33, wherein the fluid comprises a bone filler and a medicament.
- 36. (Currently Amended) The method of claim 33, wherein advancing preparing the opening in the bone using the bone tap into the bone further comprises attaching a driver to the

bone tap, placing the bone tap at an initial opening formed in the bone, and rotating the bone tap to thread the bone tap into the bone.

- 37. (Currently Amended) The method of claim 33, wherein introducing the fluid to the bone comprises coupling a fluid delivery system to the bone tap, and activating the fluid delivery system to move fluid through the bone tap and into the bone.
- 38. (Currently Amended) The method of claim 33, wherein the step of introducing the fluid to the bone comprises: (1) introducing the fluid to a first location; (2) moving the bone tap; and (3) introducing the fluid to a second location.
- 39. (Previously Presented) The method of claim 38, wherein the step of moving the bone tap comprises partially withdrawing the bone tap.
  - 40. (Currently Amended) A method of introducing a fluid into a bone, said method comprising the steps of:

providing preparing an opening in a bone using a bone tap, the bone tap comprising:

a body;

a passage through at least a portion of the body;

threading located near an end of the body; and

one or more openings through the threading in communication with the passage, the one or more openings configured to introduce bone filler into the bone;

advancing the bone tap to a first location in the bone;

introducing <u>a fluid</u> to the first bone location through the one or more openings in the bone tap;

moving the bone tap to a second location in the bone; introducing the fluid to the second bone location; and withdrawing the bone tap from the bone.

U.S. Patent Application No.: 10/717,379 Attorney Docket No.: 7177US01 Amendment Dated October 22, 2008

Page 7 of 16

41. (Previously Presented) The method of claim 40, wherein the step of moving the

bone tap to a second location comprises partially withdrawing the bone tap.

42. (Previously Presented) The method of claim 40, wherein the fluid comprises bone

cement.

43. (Previously Presented) The method of claim 40, wherein the fluid comprises a

bone filler and a medicament.

44. (Currently Amended) The method of claim 40, wherein advancing the bone tap

into to the first location in the bone comprises attaching a driver to the bone tap, placing the bone

tap at an initial opening formed in the bone, and rotating the bone tap to thread the bone tap into

the bone.

45. (Currently Amended) The method of claim 40, wherein introducing the fluid to

the first bone location comprises coupling a fluid delivery system to the bone tap, and activating

the fluid delivery system to move the fluid through the bone tap and into the bone.

46. (Previously Presented) The method of claim 40, further comprising the step of

coupling a driver to the bone tap, and using the driver to remove the bone tap from the bone.

47. (Currently Amended) A method of introducing a fluid into a bone, said method

comprising the steps of:

preparing an opening in a bone using a bone tap;

advancing [[a]] the bone tap to a first location in the bone:

introducing a fluid to the first bone location through one or more openings in the

bone tap;

moving the bone tap to a second location in the bone;

introducing the fluid to the second bone location; and

U.S. Patent Application No.: 10/717,379 Attorney Docket No.: 7177US01 Amendment Dated October 22, 2008 Page 8 of 16

withdrawing the bone tap from the bone.

- 48. (Previously Presented) The method of claim 47, wherein the step of moving the bone tap to a second location comprises partially withdrawing the bone tap.
- 49. (Previously Presented) The method of claim 47, wherein the fluid comprises bone cement.
- 50. (Previously Presented) The method of claim 47, wherein the fluid comprises a bone filler and a medicament.
- 51. (Previously Presented) The method of claim 47, wherein advancing the bone tap into the bone comprises attaching a driver to the bone tap, placing the bone tap at an initial opening formed in the bone, and rotating the bone tap to thread the bone tap into the bone.
- 52. (Currently Amended) The method of claim 47, wherein introducing the fluid to the first bone location comprises coupling a fluid delivery system to the bone tap, and activating the fluid delivery system to move the fluid through the bone tap and into the bone.
- 53. (Previously Presented) The method of claim 47, further comprising coupling a driver to the bone tap, and using the driver to remove the bone tap from the bone.